

Description:

D-System Sealer is a protective clear coat sealer. D-System Sealer provides excellent durability over plaster surfaces such as D-System plaster. D-System Sealer also offers excellent water resistance, as well as beautifying and protecting D-System Plaster.

Uses:

D-System Sealer is designed for use over D-System Plaster and other interior plaster surfaces.

Color:

White liquid

Finish:

Matte or Semi-Gloss

Packaging:

1-gallon plastic bottle- 8.5 lbs.
(3.85 kg.)

5-gallon plastic pail- 42.5 lbs.
(19-23 kg.)

Mixing:

Mix with clean drill mixer for 3 minutes or until consistent, prior to use.

Storage:

Keep from freezing. Keep out of direct sunlight for prolonged periods. Do not store at temperatures above 90°F or below 50°F.

Shelf Life:

1 year

Limitations:

D-System Sealer should be applied when surface and ambient temperatures are between 45° F and 100°F. Do not seal surface until plaster is bone dry.

Surface Preparation:

Surface must be clean and free of bond-inhibiting materials. One to 2 hours prior to application, remove all surface particulates with a moist towel. Failure to correctly prepare the surface may result in product failure.

Curing/Drying:

Drying time will vary depending on ambient temperature, humidity and thickness of application. D-System Sealer should dry to the touch within 1-3 hours, and will dry completely in 72 hours.

Application:

It is recommended that D-System Sealer is applied with a clean, soft towel. D-System Sealer may also be applied by sponge, 1/4" foam roller, or appropriate spray equipment. Two applications of D-System Sealer are required for maximum durability. First coat must dry to the touch before second coat can be applied. Strike off or roll out any obvious drips and puddles remaining after each application.

Clean Up:

Clean tools and equipment with water immediately after use.

First Aid:

SKIN CONTACT: Wash thoroughly with soap and water. EYE CONTACT: Flush immediately with water for 10-15 minutes and contact a physician.

Spills:

Wipe up with absorbent towel or rag. Wash area with water immediately.

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY.



Volterra Architectural Products,L.L.C.
1902 N 22nd Avenue
Phoenix, AZ 85009
Phone: (602) 258-7373 • Fax: (602) 258-7414