



Fino Arena (Sand Finish)

Description

Fino Arena is a 100% Acrylic Polymer Based, Opaque, crack resistant, sanded, trowel applied plaster finish.

Uses

Fino Arena may be used for interior or exterior applications over properly prepared substrates, including new or existing drywall. May also be applied over cement or gypsum basecoats or existing plaster surfaces.

Packaging

5.0 Gallon (65 lb) pail
1.0 Gallon (13 lb) pail

Colors

24 Standard colors

Custom colors available upon request.

Coverage

150 - 300 square feet
(20-24 m sq) per 5.0 Gal pail

VOC less than 30 g/L

Surface Preparation

Surface must be clean, dry, sound and free of loose material, releasing agents, efflorescence and other coatings. Remove and repair any loose paint, mortar, stucco, or concrete. Repair all cracks with a patching compound and prime the entire surface prior to application to avoid telegraphing lines appearing through the dried finish.

Mixing

Thoroughly mix the factory-prepared Fino Arena with a mixer to a homogeneous consistency. A small amount of clean, potable water may be added to adjust workability. When adding colorant packages in the field, mix thoroughly, to completely disperse all colorant. Check color against color sample for accurate match. Close container when not in use. Clean tools with water immediately after use.

Application

Fino Arena may be applied over finished and primed level 3 drywall, as a fine sand finish, or more heavily textured finish. Apply with a stainless steel trowel. Cement or gypsum brown coats should be hard floated with a cork or neoprene float to achieve best finish.

Drying Time

Fino Arena will generally dry within 3 hours. Surface absorption, temperature and humidity affect drying time

Shelf Life

Minimum of one year when stored in a cool dry location out of direct sunlight and kept from freezing.

Variance Finishes
4509 Alameda Blvd NE Suite A
Albuquerque, NM 87113
505-823-6404
www.variancefinishes.com